



THOR Tarp

DIV. OF



INTERNATIONAL, INC



DURASHIELD™ 8000 SPECIFICATIONS

DuraShield 8000 is a durable, long lasting tarp meant for roughest, toughest conditions in industry and construction.

YARN COUNT:	NOMINAL 10 X 8 TAPES/INCH (1600 DENIER TAPE)	
WEIGHT:	.044 LBS/SQUARE FOOT	
TENSILE GRAB STRENGTH:	WARP-200 LBS WEFT-170 LBS	ASTM D751 (METH.A)
TEAR STRENGTH:	WARP-60 LBS WEFT-50 LBS	ASTM D751 (METH.B)
MULLEN BURST STRENGTH:	350 P.S.I.	ASTM D751
COATING THICKNESS:	1.75 MILLS ON BOTH SIDES	
SCRIM:	BLACK TAPES	
COLOR:	BLACK OR COLORED COATING	
UV RESISTANCE:	MORE THAN 80% STRENGTH ASTM G53-84 RETENTION AFTER 2000 HOURS EXPOSURE.	

THE ABOVE PHYSICAL TEST RESULTS ARE REPRESENTATIVE DATA COLLECTED FROM A NUMBER OF PRODUCTION RUNS. RESULTS FOR AN INDIVIDUAL ROLL (BASED ON AT LEAST 3 SPECIMENS) MAY VARY FROM THE AVERAGE BY ± 10%.

To the best of our knowledge, the information contained herein is accurate. The information provided is based upon data furnished by our suppliers. However, ODIN International, Inc. assumes no liability whatsoever for the accuracy or completeness of the information contained herein. While believed to be reliable, the information of products are intended for use by skilled persons at their own risk. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that those are the only hazards that exist.

CORPORATE HQ: P.O. Box 811 • OCONOMOWOC, WI 53066-0811 • 262-569-7171 • FAX: 262-569-1511
TOLL FREE: 1-888-ODIN-INC • 1-888-634-6462 • EMAIL: INFO@THORTARP.COM

WWW.THORTARP.COM