



THOR Tarp
DIV. OF **ODIN** INTERNATIONAL, INC



DuraShield 8000 FR 4-ply Fire Retardant Polyethylene – 12 mils

DATA SHEET

DESCRIPTION	Premium flame retardant coated fabrics for industrial, construction and mining applications.	
COUNT	Nominal 12 x 9 tapes/inch	
WEIGHT	5.6 oz per square yard (190 gsm)	
TENSILE STRENGTH (Grab Method)	Warp - 150 lbs Weft - 150 lbs	ASTM D751 (Meth. A)
TEAR STRENGTH (Tongue Method)	Warp - 48 lbs Weft - 48 lbs	ASTM D751 (Meth. B)
MULLEN BURST	280 psi	ASTM D751
COATING THICKNESS	2 mil average, two sides	
SCRIM TYPE	Clear tapes	
COLOUR	Pale yellow	
WIDTH	Up to 144 inches	

Mining Certification:

FR-212A has been certified for use in mines in USA and Canada.

For USA the MSHA Certification Number is BC-141 for all types of mines.

For Canada the EM&R Certification Number is 739 for non gaseous mines.

FR-212ASTAT has been certified for use in coal mines and other gaseous mines

The EM&R Certification Number is 739-1.

CORPORATE HQ: P.O. BOX 811 • OCONOMOWOC, WI 53066-0811 • 262-569-7171 • FAX: 262-569-1511
TOLL FREE: 1-888-ODIN-INC • 1-888-634-6462 • EMAIL: INFO@THORTARP.COM

WWW.THORTARP.COM